

Description

Fastener Length: 2", Thread: 1/4-28, Thread Length: 0-63/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS517432
Minimum Qty (MOQ):	25
NSN:	5305-00-559-9224
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS517-4-32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Minimum And 2.498 Inches Maximum
Fastener Length:	2.498 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.452 Inches Minimum And 0.510 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 8630 Or Steel Comp 4037
Screw Surface Treatment:	Cadmium And Chromate
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas517 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS517-4-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.