

Description

length: 0.844", grip: 0.375", thread: 1/4-28 shear, close tolerance screw, alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS51746
Minimum Qty (MOQ):	100
NSN:	5305-00-206-0622
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS517-4-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Nominal
Fastener Length:	0.844 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.452 Inches Minimum And 0.510 Inches Maximum
Internal Drive Style:	Cross Recess Type li
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Steel Comp 4130 Or Steel Comp 8630 Or Steel Comp 8735 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response Or Mil-s-6098 Mil Spec 3rd Material Response Or Mil-s-6049 Mil Spec 4th Material Response
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS517-4-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.