

Description

Fastener Length: 2-11/64", Thread: 1/4-24, Thread Length: 9/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS517526
Minimum Qty (MOQ):	20
NSN:	5305-00-811-5077
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS517-5-26 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.518 Inches Minimum And 0.576 Inches Maximum
Fastener Length:	2.141 Inches Minimum And 2.186 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.572 Inches Minimum And 0.638 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS517-5-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.