

Description

Fastener Length: 1-33/64", Thread: 3/8-24, Thread Length: 21/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | NAS517614 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-00-206-3650 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS517-6-14 Specifications

| | |
|-------------------------------------------------------------|-----------------------------------------------------------------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.512 Inches Minimum And 0.670 Inches Maximum |
| Fastener Length: | 1.485 Inches Minimum And 1.530 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.692 Inches Minimum And 0.766 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.375 Inches |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 8630 |
| Screw Material Document And Classification: | Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS517-6-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.