

Description

Collar part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS528A4
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-827-5713
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N NAS528-A4 Specifications

Collar Outside Diameter:	0.180 Inches Minimum And 0.190 Inches Maximum
Collar Overall Height:	0.157 Inches Minimum And 0.167 Inches Maximum
Lubrication:	Grease Film
Collar Inside Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Collar Style:	Straight Type
Material:	Aluminum Alloy 2024 Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas528 Professional/industrial Association Standard

How to Order

Order this collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/NAS528-A4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.