

Description

Collar part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | NAS528A4 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-00-827-5713 |
| Schedule B: | 7616.10.9090 |
| ECCN: | 9A991 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N NAS528-A4 Specifications

| | |
|---|---|
| Collar Outside Diameter: | 0.180 Inches Minimum And 0.190 Inches Maximum |
| Collar Overall Height: | 0.157 Inches Minimum And 0.167 Inches Maximum |
| Lubrication: | Grease Film |
| Collar Inside Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Collar Style: | Straight Type |
| Material: | Aluminum Alloy 2024 Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas528 Professional/industrial Association Standard |

How to Order

Order this collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/NAS528-A4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.