

Description



NAS537B3P024

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS537B3P024
Minimum Qty (MOQ):	10
NSN:	3120-01-385-5042
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS537B3P024 Specifications

Overall Length:	0.2350 Inches Minimum And 0.2400 Inches Maximum
Body Outside Diameter:	0.3131 Inches Minimum And 0.3136 Inches Maximum
Body Inside Diameter:	0.1790 Inches Minimum And 0.1840 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Surface Finish:	63.0 Microinches Outside Diameter Surface Of Body
Material:	Copper Alloy 642 Overall
Material Document And Classification:	Astm B124 Assn Std Single Material Response Overall Or Astm B150 Assn Std Single Material Response Overall Or Astm B283 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas537 Professional/industrial Association Standard

How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS537B3P024> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.