

## **P/N NAS548P8-8**

### **Description**

Flat steel screw

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS548P88

Minimum Qty (MOQ): 50

NSN: 5305-00-515-8024

Schedule B: 7318.15.2000

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS548P8-8 Specifications

Fastener Length:	0.500 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.308 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Minimum Tensile Strength:	90000 Pounds Per Square Inch
Hardness Rating:	37.0 Rockwell C Minimum Overall
Nonmachine Thread Style:	Dog Type (type B Or C)
Countersink Angle:	100.0 Degrees Nominal
Nonmachine Nominal Thread Diameter:	0.166 Inches
Material:	Steel Overall
Material Document And Classification:	Mil-s-18729,cond N Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall

## **How to Order**

Order this tapping screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/tapping+screws/NAS548P8-8">https://military-fasteners.com/screws/tapping+screws/NAS548P8-8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/hAS548P8-8">https://military-fasteners.com/screws/hAS548P8-8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/hAS548P8-8">https://military-fasteners.com/screws/hAS548P8-8</a> and selecting the quantity you