

**Description**

Fastener Length: 1/4", Thread: 8-32, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS5502U4
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-188-9934
Schedule B:	8108.90.3060
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N NAS5502U4 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.250 Inches Nominal
<b>Fastener Length:</b>	0.220 Inches Minimum And 0.250 Inches Maximum
<b>Head Style:</b>	Fillister
<b>Head Diameter:</b>	0.265 Inches Minimum And 0.270 Inches Maximum
<b>Head Height:</b>	0.088 Inches Minimum And 0.102 Inches Maximum
<b>Internal Drive Style:</b>	Tri-wing Recess
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Screw Material:</b>	Titanium
<b>Screw Material Document And Classification:</b>	Ams4928,8al-4v Assn Std Single Material Response Or Ams4967,8al-4v Assn Std Single Material Response
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas5502 Professional/industrial Association Standard

## How to Order

Order this screws from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5502U4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.