

Description

Fastener Length: 5/16", Thread: 8-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS5502U5
Minimum Qty (MOQ):	20 EA
NSN:	5305-01-191-7455
Schedule B:	8108.90.3060
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS5502U5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.312 Inches Nominal
Fastener Length:	0.282 Inches Minimum And 0.312 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.265 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.088 Inches Minimum And 0.102 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Titanium
Screw Material Document And Classification:	Ams4928,8al-4v Assn Std Single Material Response Or Ams4967,8al-4v Assn Std Single Material Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas5502 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5502U5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.