

P/N NAS5503U16

Description

Thread: 10-32, Material: Titanium, Tensile Strength: 160000, Head Style: Fillister, NAS5503U series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS5503U16

Minimum Qty (MOQ):

NSN: 5305-01-188-9952

Schedule B: 8108.90.3060

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N NAS5503U16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.000 Inches Nominal
Fastener Length:	0.970 Inches Minimum And 1.000 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.306 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.103 Inches Minimum And 0.118 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Titanium Alloy
Screw Material Document And Classification:	Ams4928,6al-4v Assn Std Single Material Response Or Ams4967,6al-4v Assn Std Single Material Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas5503 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS5503U16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS5503U16 and selecting the quantity you