

**Description**

Fastener Length: 1/4", Thread: 10-32, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS5503U4
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-188-9963
Schedule B:	8108.90.3060
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N NAS5503U4 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.250 Inches Nominal
<b>Fastener Length:</b>	0.220 Inches Minimum And 0.250 Inches Maximum
<b>Head Style:</b>	Fillister
<b>Head Diameter:</b>	0.306 Inches Minimum And 0.313 Inches Maximum
<b>Head Height:</b>	0.103 Inches Minimum And 0.118 Inches Maximum
<b>Internal Drive Style:</b>	Tri-wing Recess
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Screw Material:</b>	Titanium Alloy
<b>Screw Material Document And Classification:</b>	Ams4928,6al-4v Assn Std Single Material Response Or Ams4967,6al-4v Assn Std Single Material Response
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas5503 Professional/industrial Association Standard

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5503U4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.