



Military-Fasteners.com

P/N NAS5503U6

Description

Fastener Length: 3/8", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS5503U6
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-191-7461
Schedule B:	8108.90.3060
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS5503U6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.375 Inches Nominal
Fastener Length:	0.345 Inches Minimum And 0.375 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.306 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.103 Inches Minimum And 0.118 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Titanium Alloy
Screw Material Document And Classification:	Ams4928,6al-4v Assn Std Single Material Response Or Ams4967,6al-4v Assn Std Single Material Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas5503 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5503U6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.