



Military-Fasteners.com

P/N NAS5600-4

Description

Fastener Length: 1/4", Thread: 4-40, Thread Length: 13/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS56004
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-505-2847
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS5600-4 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.126 Inches Minimum And 0.206 Inches Maximum
<b>Fastener Length:</b>	0.220 Inches Minimum And 0.250 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.193 Inches Minimum And 0.226 Inches Maximum
<b>Internal Drive Style:</b>	Tri-wing Recess
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas5600 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS5600-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.