

P/N NAS5601-7

Description

Fastener Length: 7/16", Thread: 6-32, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS56017
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-185-2829
Schedule B:	7318.15.6080
ECCN:	EAR99



^{*} See page 2 for technical characteristics

P/N NAS5601-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.440 Inches Nominal
Fastener Length:	0.440 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.280 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams 6322 Assn Std 2nd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty lii Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas5601 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS5601-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.