

# **P/N NAS5602-10**

### **Description**

Fastener Length: ", Thread: 8-32, Thread Length: "

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS560210
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-193-6253
Schedule B:	7318.15.6080
ECCN:	EAR99



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS5602-10 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.620 Inches Nominal
Fastener Length:	0.620 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.280 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams 6322 Assn Std 2nd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty Iii Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas5602 Professional/industrial Association Standard

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS5602-10">https://military-fasteners.com/bolts/machine+bolts/NAS5602-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.