

**Description**

Fastener Length: 1/2", Thread: 10-32, Thread Length: 13/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS56038
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-392-0833
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS5603-8 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.326 Inches Minimum And 0.418 Inches Maximum
<b>Fastener Length:</b>	0.470 Inches Minimum And 0.500 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.338 Inches Minimum And 0.381 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp E4340 Or Steel Comp 4340 Or Steel Comp 8740
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas5603 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS5603-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.