



Military-Fasteners.com

P/N NAS5604-10

Description

Fastener Length: 5/8", Thread: 1/4-28, Thread Length: 33/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS560410
Minimum Qty (MOQ):	25 EA
NSN:	5305-01-304-2900
Schedule B:	7318.15.6080
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS5604-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.499 Inches Minimum And 0.529 Inches Maximum
Fastener Length:	0.610 Inches Minimum And 0.640 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.456 Inches Minimum And 0.506 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.2500 Inches
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams6322 Assn Std 2nd Material Response
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec 1st Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas5604 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS5604-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.