

Description

Fastener Length: 1-1/4", Thread: 1/4-28, Thread Length: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS560420 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-185-6270 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |



* See page 2 for technical characteristics

P/N NAS5604-20 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.250 Inches Nominal |
| Fastener Length: | 1.250 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.508 Inches Maximum |
| Internal Drive Style: | Tri-wing Recess |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 4340 Or Steel Comp 8740 |
| Screw Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams 6322 Assn Std 2nd Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty Iii Cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas5604 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS5604-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.