

**Description**

Fastener Length: 7/16", Thread: 8-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS560CK20
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-251-8258
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS560CK2-0 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.327 Inches Minimum And 0.372 Inches Maximum
<b>Fastener Length:</b>	0.395 Inches Minimum And 0.440 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.287 Inches Minimum And 0.334 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	85000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 304 Or Steel Comp 321 Or Steel Comp 347
<b>Screw Material Document And Classification:</b>	Qq-s-763,cond A Fed Spec 1st Material Response Or Qq-s-763 Fed Spec 2nd Material Response Or Qq-s-763,cond A Fed Spec 3rd Material Response
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560CK2-0> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.