

Description

Fastener Length: 7/16", Thread: 8-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS560CK20
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-251-8258
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS560CK2-0 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.327 Inches Minimum And 0.372 Inches Maximum
Fastener Length:	0.395 Inches Minimum And 0.440 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.287 Inches Minimum And 0.334 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	85000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 304 Or Steel Comp 321 Or Steel Comp 347
Screw Material Document And Classification:	Qq-s-763,cond A Fed Spec 1st Material Response Or Qq-s-763 Fed Spec 2nd Material Response Or Qq-s-763,cond A Fed Spec 3rd Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560CK2-0> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.