



Military-Fasteners.com

P/N NAS560CK2P1

Description

Fastener Length: 1/2", Thread: 8-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS560CK2P1
Minimum Qty (MOQ):	45 EA
NSN:	5305-00-050-1092
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS560CK2P1 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.440 Inches Minimum And 0.502 Inches Maximum
Fastener Length:	0.457 Inches Minimum And 0.502 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.287 Inches Minimum And 0.334 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	75000 Pounds Per Square Inch
Hardness Rating:	248.0 Brinell Standard Minimum And 321.0 Brinell Standard Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 304 Or Steel Comp 321 Or Steel Comp 347 Or Steel Corrosion Resisting
Screw Material Document And Classification:	Qq-s-763 Fed Spec 1st Material Response Or Qq-s-763 Fed Spec 2nd Material Response Or Mil-s-763 Fed Spec 3rd Material Response Or 10 Fscm 71321 Mfr Ref Single Material Response
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560CK2P1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.