

Description

Fastener Length: 47/64", Thread: 10-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS560CK34
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-082-3299
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS560CK3-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.433 Inches Minimum And 0.508 Inches Maximum
Fastener Length:	0.698 Inches Minimum And 0.743 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.337 Inches Minimum And 0.387 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
iii Part Name Assigned By Controlling Agency:	Navy Special Project
Screw Material:	Steel Comp 304 Or Steel Comp 321 Or Steel Comp 347 Or Steel Comp 384
Screw Material Document And Classification:	Qq-s-763 Fed Spec 1st Material Response Or Qq-s-763 Fed Spec 2nd Material Response Or Qq-s-763 Fed Spec 3rd Material Response
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas560 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560CK3-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.