

**Description**

length: 0.463", thread: 10-32 - structural machine screw - 100°, flush head - corrosion resistant steel - philips recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS560CK3P0
Minimum Qty (MOQ):	10
NSN:	5305-00-722-2683
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS560CK3P0 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.431 Inches Maximum
<b>Fastener Length:</b>	0.448 Inches Minimum And 0.493 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.337 Inches Minimum And 0.387 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	75000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 304 Or Steel Comp 321 Or Steel Comp 347
<b>Screw Material Document And Classification:</b>	Qq-s-763 Fed Spec All Material Responses
<b>Screw Surface Treatment:</b>	Cadmium
<b>Thread Series Designator:</b>	Unf
<b>Specification/standard Data:</b>	80205-nas560 Professional/industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS560CK3P0> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.