



Military-Fasteners.com

P/N NAS560CK3P0

Description

length: 0.463", thread: 10-32 - structural machine screw - 100°, flush head - corrosion resistant steel - philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS560CK3P0
Minimum Qty (MOQ):	10
NSN:	5305-00-722-2683
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS560CK3P0 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.431 Inches Maximum
Fastener Length:	0.448 Inches Minimum And 0.493 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.337 Inches Minimum And 0.387 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	75000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 304 Or Steel Comp 321 Or Steel Comp 347
Screw Material Document And Classification:	Qq-s-763 Fed Spec All Material Responses
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas560 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS560CK3P0> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.