



Military-Fasteners.com

P/N NAS560CK3P2

Description

Fastener Length: 39/64", Thread: 10-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS560CK3P2
Minimum Qty (MOQ):	45 EA
NSN:	5305-00-571-9516
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS560CK3P2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.433 Inches Minimum And 0.508 Inches Maximum
Fastener Length:	0.573 Inches Minimum And 0.618 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.337 Inches Minimum And 0.387 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 304 Or Steel Comp 321 Or Steel Comp 347
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas560 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560CK3P2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.