

Description

Fastener Length: 43/64", Thread: 1/4-28

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | NAS560CK4P2 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5305-01-571-9689 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS560CK4P2 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.636 Inches Minimum And 0.681 Inches Maximum |
| Head Style: | Oval Countersunk |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 75000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 304 Or Steel Comp 347 Or Steel |
| Screw Material Document And Classification: | Qq-s-763 Fed Spec All Material Responses |
| Screw Surface Treatment: | Cadmium |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560CK4P2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.