

Description

Fastener Length: 1-9/16", Thread: 8-32, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS560HK218
Minimum Qty (MOQ):	130 EA
NSN:	5305-01-015-6613
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS560HK2-18 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.380 Inches Minimum And 0.455 Inches Maximum
Fastener Length:	1.520 Inches Minimum And 1.565 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.287 Inches Minimum And 0.334 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5733 Assn Std 1st Material Response Or Ams 5732 Assn Std 2nd Material Response
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas560 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560HK2-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.