

## Description

Fastener Length: 1-11/16", Thread: 8-32, Thread Length: 29/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS560HK220
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-015-6614
Schedule B:	7318.15.4000
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS560HK2-20 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.380 Inches Minimum And 0.455 Inches Maximum
<b>Fastener Length:</b>	1.645 Inches Minimum And 1.690 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.287 Inches Minimum And 0.334 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	140000 Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Material Document And Classification:</b>	Ams 5733 Assn Std 1st Material Response Or Ams 5732 Assn Std 2nd Material Response
<b>Thread Series Designator:</b>	Unc
<b>Specification/standard Data:</b>	80205-nas560 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560HK2-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.