



Military-Fasteners.com

P/N NAS560HK2-4

Description

Fastener Length: 11/16", Thread: 8-32, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS560HK24
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-950-0072
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS560HK2-4 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.380 Inches Minimum And 0.455 Inches Maximum
Fastener Length:	0.645 Inches Minimum And 0.690 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.287 Inches Minimum And 0.334 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Hardness Rating:	248.0 Brinell Standard Minimum And 341.0 Brinell Standard Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5735 Assn Std 1st Material Response Or Ams 5733 Assn Std 2nd Material Response
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas560 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560HK2-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.