

Description

Fastener Length: 3/4", Thread: 8-32, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS560HK25 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5305-01-064-5432 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS560HK2-5 Specifications

| | |
|-------------------------------------|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.380 Inches Minimum And 0.455 Inches Maximum |
| Fastener Length: | 0.707 Inches Minimum And 0.752 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.287 Inches Minimum And 0.334 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 140000 Pounds Per Square Inch |
| Hardness Rating: | 24.0 Rockwell C Minimum And 35.0 Rockwell C Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Screw Material: | Iron Alloy 660 |
| Thread Series Designator: | Unc |
| Specification/standard Data: | 80205-nas560 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560HK2-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.