

Description

length: 0.526", thread: 10-32, structural, flush head, corrosion resistant steel, philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS560HK31
Minimum Qty (MOQ):	25
NSN:	5305-00-916-4241
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS560HK3-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.494 Inches Minimum And 0.556 Inches Maximum
Fastener Length:	0.511 Inches Minimum And 0.556 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.337 Inches Minimum And 0.387 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Hardness Rating:	248.0 Brinell Standard Minimum And 321.0 Rockwell Superficial 15-n Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Iron Alloy 660
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS560HK3-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.