

Description

Fastener Length: 1-7/64", Thread: 10-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS560HK310
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-818-8319
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS560HK3-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.371 Inches Minimum And 0.508 Inches Maximum
Fastener Length:	1.073 Inches Minimum And 1.118 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.337 Inches Minimum And 0.387 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	248.0 Brinell Standard Minimum And 321.0 Brinell Standard Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Iron Alloy 660 Or Steel Comp 630
Screw Material Document And Classification:	Ams 5732 Assn Std 1st Material Response Or Ams 5733 Assn Std 2nd Material Response
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560HK3-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.