

Description

length: 0.651", grip: 0.188", thread: 10-32, structural machine screw, flush head, corrosion resistant steel, philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS560HK3P3
Minimum Qty (MOQ):	25
NSN:	5305-00-628-7822
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS560HK3P3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.371 Inches Minimum And 0.508 Inches Maximum
Fastener Length:	0.636 Inches Minimum And 0.681 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.337 Inches Minimum And 0.387 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Hardness Rating:	248.0 Brinell Standard Minimum And 321.0 Brinell Standard Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5732 Assn Std 1st Material Response Or Ams 5733 Assn Std 2nd Material Response
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS560HK3P3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.