



Military-Fasteners.com

P/N NAS560HK3P4

## Description

Fastener Length: 47/64", Thread: 10-32, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS560HK3P4
Minimum Qty (MOQ):	35 EA
NSN:	5305-00-882-9189
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS560HK3P4 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.371 Inches Minimum And 0.508 Inches Maximum
<b>Fastener Length:</b>	0.698 Inches Minimum And 0.743 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.337 Inches Minimum And 0.387 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	140000 Pounds Per Square Inch
<b>Hardness Rating:</b>	248.0 Brinell Standard Minimum And 321.0 Brinell Standard Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Material Document And Classification:</b>	Ams 5735 Assn Std 1st Material Response Or Ams 5733 Assn Std 2nd Material Response
<b>Screw Surface Treatment:</b>	Cadmium
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560HK3P4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.