



★ FASTENERS

Military-Fasteners.com

P/N NAS560HK3P8

Description

Fastener Length: 63/64", Thread: 10-32, Thread Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS560HK3P8 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-629-4165 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |



* See page 2 for technical characteristics

P/N NAS560HK3P8 Specifications

| | |
|--|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.485 Inches Minimum And 0.515 Inches Maximum |
| Fastener Length: | 0.948 Inches Minimum And 0.993 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.337 Inches Minimum And 0.387 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 130000 Pounds Per Square Inch |
| Hardness Rating: | 248.0 Brinell Standard Minimum And 341.0 Brinell Standard Maximum |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Iron Alloy 660 |
| Screw Material Document And Classification: | Ams 5733 Assn Std 1st Material Response Or Ams 5732 Assn Std 2nd Material Response |
| Screw Surface Treatment: | Cadmium |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS560HK3P8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.