



Military-Fasteners.com

P/N NAS560HK4-6

Description

Fastener Length: 59/64", Thread: 1/4-28, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS560HK46
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-984-1640
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS560HK4-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.496 Inches Minimum And 0.571 Inches Maximum
Fastener Length:	0.886 Inches Minimum And 0.931 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.452 Inches Minimum And 0.510 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 7478 Assn Std Single Material Response
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas560 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560HK4-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.