



Military-Fasteners.com

P/N NAS560XK2P8

Description

Fastener Length: 29/32", Thread: 8-32, Thread Length: 27/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS560XK2P8 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-361-7498 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS560XK2P8 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.833 Inches Minimum And 0.940 Inches Maximum |
| Fastener Length: | 0.895 Inches Minimum And 0.940 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.323 Inches Minimum And 0.334 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Nickel Alloy X-750 |
| Screw Material Document And Classification: | Ams5668 Assn Std Single Material Response |
| Screw Surface Treatment: | Cadmium |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas560 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560XK2P8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.