

P/N NAS560XK3-7

Description

Fastener Length: 59/64", Thread: 10-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS560XK37

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-042-4410

Schedule B: 7508.90.5000

ECCN: 9A991

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc



^{*} See page 2 for technical characteristics

P/N NAS560XK3-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.433 Inches Minimum And 0.508 Inches Maximum
Fastener Length:	0.886 Inches Minimum And 0.931 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.337 Inches Minimum And 0.387 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Nickel Alloy X-750
Screw Material Document And Classification:	Ams 5668 Assn Std Single Material Response
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas560 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS560XK3-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS560XK3-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS560XK3-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS560XK3-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/nas60XK3-7 and selecting the quantity you want then click "add to cart".