

Description

Fastener Length: 59/64", Thread: 10-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | NAS560XK37 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-042-4410 |
| Schedule B: | 7508.90.5000 |
| ECCN: | 9A991 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |

NO IMAGE
AVAILABLE

P/N NAS560XK3-7 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.433 Inches Minimum And 0.508 Inches Maximum |
| Fastener Length: | 0.886 Inches Minimum And 0.931 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.337 Inches Minimum And 0.387 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Screw Material: | Nickel Alloy X-750 |
| Screw Material Document And Classification: | Ams 5668 Assn Std Single Material Response |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas560 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560XK3-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.