

Description

Fastener Length: 1-39/64", Thread: 10-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS560XK3P18
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-958-8262
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

P/N NAS560XK3P18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.433 Inches Minimum And 0.508 Inches Maximum
Fastener Length:	1.573 Inches Minimum And 1.618 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.337 Inches Minimum And 0.387 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Nickel Alloy X-750
Screw Surface Treatment:	Cadmium
Special Features:	Cadmium Flash
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas560 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560XK3P18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.