

**Description**

Fastener Length: 1-39/64", Thread: 10-32, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS560XK3P18
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-958-8262
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE  
AVAILABLE

## P/N NAS560XK3P18 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.433 Inches Minimum And 0.508 Inches Maximum
<b>Fastener Length:</b>	1.573 Inches Minimum And 1.618 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.337 Inches Minimum And 0.387 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Nickel Alloy X-750
<b>Screw Surface Treatment:</b>	Cadmium
<b>Special Features:</b>	Cadmium Flash
<b>Thread Series Designator:</b>	Unf
<b>Specification/standard Data:</b>	80205-nas560 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560XK3P18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.