

Description

Fastener Length: 51/64", Thread: 10-32, Thread Length: 51/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS560XK3P5
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-361-7499
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS560XK3P5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.698 Inches Minimum And 0.805 Inches Maximum
Fastener Length:	0.760 Inches Minimum And 0.805 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.375 Inches Minimum And 0.387 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
iii Part Name Assigned By Controlling Agency:	Navy Special Project
Screw Material:	Nickel Alloy X-750
Screw Material Document And Classification:	Ams5668 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas560 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560XK3P5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.