

Description

Fastener Length: 55/64", Thread: 10-32, Thread Length: 55/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS560XK3P6 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-361-7500 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |



* See page 2 for technical characteristics

P/N NAS560XK3P6 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.761 Inches Minimum And 0.868 Inches Maximum |
| Fastener Length: | 0.823 Inches Minimum And 0.868 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.375 Inches Minimum And 0.387 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Part Name Assigned By Controlling Agency: | Navy Special Project |
| Screw Material: | Nickel Alloy X-750 |
| Screw Material Document And Classification: | Ams5668 Assn Std Single Material Response |
| Screw Surface Treatment: | Cadmium |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas560 Professional/Industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS560XK3P6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.