

**Description**

Diameter: 3/32", Length: 7/8", steel comp 1070or steel comp 1074or steel comp 1080or steel comp 1086or steel comp 1095 overall

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS561P315                                |
| Minimum Qty (MOQ):      | 80 EA                                     |
| NSN:                    | 5315-00-271-7513                          |
| National Motor Freight: | 094380, Cotter Pins / Spring Cotters Iron |

NO IMAGE  
AVAILABLE

## P/N NAS561P3-15 Specifications

|   |   |
|---|---|
| <b>Overall Length:</b>                                | 0.937 Inches Nominal  |
| <b>Diameter:</b>                                      | 0.099 Inches Minimum And 0.103 Inches Maximum   |
| <b>Material Thickness:</b>                            | 0.022 Inches Nominal  |
| <b>Hardness Rating:</b>                               | 46.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall   |
| <b>Material:</b>                                      | Steel Comp 1070 Overall Or Steel Comp 1074 Overall Or Steel Comp 1080 Overall Or Steel Comp 1086 Overall Or Steel Comp 1095 Overall |
| <b>Material Document And Classification:</b>          | 66 Fed Std All Material Responses Overall   |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty2 Cl2 Fed Spec Single Treatment Response Overall   |
| <b>Style Designator:</b>                              | Slotted   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS561P3-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.