

Description

Fastener Length: 31/32", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 29/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS56331 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-00-836-7069 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS563-31 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.907 Inches Minimum |
| Fastener Length: | 0.969 Inches Minimum |
| Head Style: | Hexagon |
| Head Height: | 0.188 Inches Nominal |
| Width Between Flats: | 0.365 Inches Minimum And 0.377 Inches Maximum |
| Hole Diameter: | 0.047 Inches Nominal |
| Nominal Thread Diameter: | 0.190 Inches |
| Hole Quantity: | 6 |
| Hole Type: | Drilled |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Hole Configuration Style: | Hexagon Longitudinal Hole |
| Material: | Steel Comp 4037 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas563 Professional/industrial Association Standard |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS563-31> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.