

Description

Fastener Length: 1-3/8", Hole Diameter: 5/64", Thread: 10-32, Thread Length: 1-5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS56343
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-115-3408
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS563-43 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.298 Inches Minimum And 1.315 Inches Maximum
Fastener Length:	1.328 Inches Minimum And 1.375 Inches Maximum
Head Style:	Hexagon
Head Height:	0.188 Inches Nominal
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Hole Quantity:	3
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Corners
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8640 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas563 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS563-43> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.