

Description

Fastener Length: 41/64", Hole Diameter: 1/16", Thread: 10-32, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS563C19
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-039-9716
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS563C19 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.456 Inches Minimum And 0.595 Inches Maximum
Fastener Length:	0.594 Inches Minimum And 0.641 Inches Maximum
Head Style:	Hexagon
Head Height:	0.188 Inches Nominal
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Hole Quantity:	3
Hole Type:	Drilled
Features Provided:	Unfinished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Corners
Material:	Steel Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas563 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS563C19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.