

Description

Fastener Length: 1-1/2", Hole Diameter: 5/64", Thread: 10-32, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS563C33
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-308-2839



P/N NAS563C33 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.971 Inches Minimum And 1.001 Inches Maximum
Fastener Length:	1.453 Inches Minimum And 1.500 Inches Maximum
Head Style:	Hexagon
Head Height:	0.178 Inches Minimum And 0.198 Inches Maximum
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.030 Inches Minimum And 0.060 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Corners
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas563 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS563C33> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.