

## P/N NAS564-45

## **Description**

Fastener Length: 1-3/8", Hole Diameter: 1/16", Thread: 1/4-28, Thread Length: 1-3/8

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS56445

Minimum Qty (MOQ):

NSN: 5306-00-550-0487

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







# **P/N NAS564-45 Specifications**

| Thread Class:                                  | 3a   |
|--|--|
| Thread Direction:                              | Right-hand   |
| Thread Length:                                 | 1.346 Inches Minimum And 1.376 Inches Maximum  |
| Fastener Length:                               | 1.406 Inches Nominal   |
| Head Style:                                    | Hexagon  |
| Head Height:                                   | 0.219 Inches Nominal   |
| Width Between Flats:                           | 0.438 Inches Nominal   |
| Hole Diameter:                                 | 0.070 Inches Nominal   |
| Nominal Thread Diameter:                       | 0.250 Inches   |
| Grip Length:                                   | 0.030 Inches Minimum And 0.060 Inches Maximum  |
| Hole Quantity:                                 | 6  |
| Hole Type:                                     | Drilled  |
| Features Provided:                             | Finished Head  |
| Thread Quantity Per Inch:                      | 28   |
| Minimum Tensile Strength:                      | 160000 Pounds Per Square Inch  |
| Hardness Rating:                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  |
| Hole Configuration Style:                      | Hexagon Longitudinal Hole  |
| Material:                                      | Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall |
| Material Document And Classification:          | Mil-b-6812 Mil Spec All Material Responses Overall   |
| Surface Treatment:                             | Cadmium Overall And Chromate Overall   |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall  |
| Thread Series Designator:                      | Unf  |
|  |  |

## **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS564-45">https://military-fasteners.com/bolts/machine+bolts/NAS564-45</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS564-45">https://military-fasteners.com/bolts/machine+bolts/NAS564-45</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS564-45">https://military-fasteners.com/bolts/machine+bolts/NAS564-45</a>